

TECHNICAL DATASHEET**DEKAFINISHER****PRODUCT**

Dekafinisher is a water based smoothing agent. A ready-mixed, mild, neutral spray for smoothing joints that remain in sight, to be used directly after the application of Dekasyt adhesives and sealants.

APPLICATIONS

- Smoothing of freshly applied visible joints.

FEATURES

- Perfect end result.
- Ready to use.
- Compatible with paints and coatings.

TECHNICAL DATA

Specific density (20°C)	: approximately 1,02 kg/liter
Colour	: transparent
Application temperature	: +5°C to +35°C
Packaging	: 500 ml spray bottle

METHOD OF USE

Shake the spray bottle before use. Spray the surface with Dekafinisher after application of the adhesive or sealant. Smooth joints with a spatula, trowel, PVC pipe or finger. After using **Dekafinisher**, it is recommended to rinse the surface with normal water and remove any residue in order to prevent streaks. This step is absolutely recommended if the smoothed joints are to be painted afterwards. **Dekafinisher** is not free of paint interfering substances, this can have a negative influence on the adhesion of the coatings.

STORAGE STABILITY

Dekafinisher is not frost resistant and should be stored between +5°C and +30°C. The packaging must be protected from direct sunlight and heat. Unopened packaging can be stored for 24 months in a cool and dry place.

SAFETY PRECAUTIONS

Consult our latest safety data sheet for more details.

TRANSPORT CLASSIFICATION

Consult our latest safety data sheet for more details.

©Dekalin August, 2016